



# Safety Data Sheet

## SECTION 1: Identification

**Product Name** Qwik Seal Liquid Polymer  
**Product Code** 22-83  
**Recommended use** Liquid wax for auto, marine and aircraft paint

**Manufacturer** Mark V Products  
 400 El Sobrante Road  
 Corona, CA 92879  
 (951) 280-9799

**Emergency Phone #**  
 Chemtrec (800) 424-9300

## SECTION 2: Hazard Identification

**Physical State:** Liquid  
**Color:** Yellow  
**Odor:** Vanilla

**GHS Classification:**  
 Flammability: Category 4  
 Skin Irritation: Category 3  
 Eye Irritation: Category 2B  
 Specific Target Organ toxicity  
 Single Exposure: None  
 Aspiration Hazard: Category 2



**Signal Word:** **WARNING**

**Physical Hazard:** H227: Combustible Liquid

**Health Statements:** H303: May be harmful if swallowed  
 H305: May be harmful if swallowed and enters airways  
 H317: May cause an allergic skin reaction

**Precautionary Statements:** P261: Avoid breathing fumes / dust  
 P270: Do not eat drink or smoke when using this product  
 P280: Wear protective gloves and eye protection when using this product

**Response:** P301+P330+P331. If swallowed, rinse mouth. Do not induce vomiting  
 P304+340 If inhaled, Remove person to fresh air and keep comfortable for breathing  
 P332+P313 If skin irritation occurs, get medical attention  
 P337+313: If eye irritation persists get medical advice/attention

**Exposure routes** Inhalation, Skin contact, Eye Contact, Ingestion

**Eye Contact:** May cause mild eye irritation. Symptoms include stinging, tearing, and redness.

**Skin Contact:** May cause mild skin irritation. Prolonged or repeated contact may dry the skin. Symptoms may include redness, burning, drying and cracking of skin.

**Ingestion:** May be harmful if swallowed. Can cause gastrointestinal irritation, nausea, vomiting & diarrhea. Aspiration of material into lungs may cause chemical pneumonitis.

**Inhalation:** Excessive inhalation of vapors can cause nasal and respiratory irritation.

**Label Elements:**

**Precautionary Statements** P102: Keep out of the reach of children

**Storage / Disposal** Dispose of according to local, regional and/or national regulations.

## SECTION 3: Composition / Information on Ingredients

HAZARDOUS INGREDIENT	CAS NUMBER	%
Petroleum Distillate	64742-47-8	10 - 25
Petroleum Distillate	64742-48-9	0 - 15

## SECTION 4: First Aid Measures

### Description of first aid measures

Inhalation	Move Victim to fresh air and get medical attention if you feel unwell. Administer oxygen if breathing is difficult. Give artificial respiration if victim is not breathing and get immediate medical attention.
Skin	Wash with soap and water. Remove contaminated clothing and wash before re-use.
Eye	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue Rinsing. If eye irritation persists: Get medical attention.
Ingestion	Do not induce vomiting. Rinse mouth and drink two glasses of water. Call physician if you feel unwell.

### Most important systems and effects, both acute and delayed

Product may cause drying of skin. Wear nitrile or rubber gloves when using product.

### Indication of any immediate medical attention and special treatment needed

Note to Physician All treatments should be based on observed signs and symptoms of distress in the patient.

## SECTION 5: Fire Fighting Measures

### Extinguishing media

Suitable Extinguishing Media CO<sub>2</sub>, dry chemical, foam, water fog, water spray

Unsuitable Extinguishing Media None

### Special hazards arising from the substance or mixture

Unusual Fire and Explosion Hazards None

Hazardous Combustion Products Combustion may produce Carbon Monoxide, CO<sub>2</sub> and potentially irritating fumes.

### Advice for firefighters

Wear approved SCBA with full facepiece operated in positive pressure demand mode.  
Hazardous Polymerization is not expected to occur  
Avoid contact with strong oxidizing agents and strong acids

## SECTION 6: Accidental Release Measures

### Personal precautions, protective equipment and emergency procedures

Personal Precautions For large spills (500 gallons or more) wear appropriate protective equipment including rubber boots, gloves, goggles and apron.

Emergency Procedures Turn off all sources of ignition. (pilot lights, flares, etc.)

Environmental Precautions Avoid run off to waterways and storm drains.

### Methods and materials for containment and clean up

Containment / Clean up Measures Stop leak if you can do it without risk. Dike ahead of liquid spill to prevent entering storm drains. Absorb and transfer to containers.

## SECTION 7: Handling and Storage

### Precautions for safe handling

Handling Product is slippery. If product is spilled onto floor, clean area to prevent slipping.

### Conditions for safe storage, including any incompatibilities

Storage Store in a cool, dry place.

**Incompatible Materials or Ignition Sources**

Keep away from oxidizers and strong acids

## SECTION 8: Exposure Controls / Personal Protection

### Exposure Controls

#### Engineering

#### Measures / Controls

None needed when used as directed.

#### Personal Protective Equipment

Safety goggles, nitrile gloves, dust mask

#### General Industrial Hygiene

#### Considerations

None needed when used as directed

## SECTION 9: Physical and Chemical Properties

### Information on Physical and Chemical Properties

<b>Physical Form</b>	Liquid	<b>Appearance</b>	Creamy liquid
<b>Color</b>	Yellow	<b>Odor</b>	Vanilla
<b>Taste</b>	Data Lacking	<b>Particulate Type</b>	N/A
<b>Particulate Size</b>	N/A	<b>Aerosol Type</b>	N/A

### General Properties

<b>Boiling Pt</b>	240 F	<b>Melting Point</b>	Data Lacking
<b>pH</b>	8.0 - 9.0	<b>SG / Density</b>	0.89 - 0-91
<b>Water Solubility %</b>	70	<b>Flash Pt.</b>	145 F

## SECTION 10: Stability and Reactivity

<b>Reactivity</b>	No dangerous reaction know under conditions of normal use
<b>Chemical stability</b>	Stable under normal temperatures and pressures.
<b>Possibility of hazardous reactions</b>	Hazardous polymerization is not expected to occur
<b>Conditions to Avoid</b>	High temperatures, freezing temperatures
<b>Hazardous Decomposition</b>	Combustion may produce Carbon Monoxide, CO <sub>2</sub> and potentially irritating fumes

## SECTION 11: Toxicological Information

**Acute Toxicity:** Estimated to be above 5,000 mg/kg

**Component Information:** See Section 3

#### Specific effects

<b>Carcinogenic effects:</b>	None known
<b>Mutagenic effects:</b>	None known
<b>Reproductive toxicity:</b>	None known
<b>Target organ effects:</b>	None known

## SECTION 12: Ecological Information

**Environmental Information:** Do not allow product to containmate ground water system.

Petroleum Distillate 64742-47-8 Toxicity to Fish. LC50: 45 mg / L Pimephales promelas 96 h flow through.  
LC50: 4720 mg / L Dendronereides heteropoda 96 h

## SECTION 13: Disposal Considerations

Dispose of according to local, state and federal regulations.

## SECTION 14: Transport Information

Product is not regulated by DOT for ground and ocean transport.

## SECTION 15: Regulatory Information

This product is not subject to reporting requirements for SARA 313, SARA 311/312, Clean Water Act, and CERCLA

**California Proposition 65:** This product is not subject to the reporting requirements under California's Proposition 65

## SECTION 16: Other Information

Dated : December 24, 2019

**WARNING:** This information contained in this SDS is based on the data available to us from sources we believe to be reliable. No warranty or guaranty expressed or implied is made regarding the accuracy of this data or the results obtained from the reliance on this data. The manufacturer assumes no responsibility for injury from the use of this product. Be safe: Read this safety information and forward it to all persons who may be exposed to this product.